

EUREKA HEAT FR

PRODUCT CODE: E13-4HFR



Product Information:

- Eureka Heat FR arc flash resistance glove is Arc Flash Certified to ASTM F2675 ATPV:
 - 60% black nitrile coating = 30 Cal/cm²
 - 25% white print (back) = 23 Cal/cm²
 - 15% green liner fabric = 5.8 Cal/cm²
 With the garments ATPV level reaching NFPA 70E = Level 1 > 4 cal/cm² (=16.8 joules/cm²).
- EN407 Heat Resistant to contact heat 100°C.
- High cut resistance EN388 Level 5 / E Cut Protection, ISO 13997 = 24.4N.
- Seamless knit para-aramid, FR polyester and chloroprene composite. Comfortable, close fitting, high dexterity glove. Is inherently fire retardant with an extended cuff for increased protection.
- Oil and water repellent nitrile coating.

Applications:

- Work on Switch Boards and Electrical Panels
- Electrical Facilities Maintenance
- Emergency Services/Rural Fire
- Oil and Gas Works
- Working with Hot and Sharp Objects

Physical Dimensions:

| SIZE | PALM WIDTH | GLOVE LENGTH |
|------|------------|--------------|
| S | 8CM +/- | 24.5CM +/- |
| M | 9CM +/- | 25CM +/- |
| L | 10CM +/- | 25.5CM +/- |
| XL | 11CM +/- | 26CM +/- |
| 2XL | 12CM +/- | 26.5CM +/- |
| 3XL | CM +/- | CM +/- |

Available In:

| PRODUCT CODE | UOM | MOQ | CTN QTY |
|-----------------|------|-----|---------|
| E13-4HFR-(SIZE) | PAIR | 1 | 60 |

Standards:

EN 388 EN 407






ISO 13997
24.4 Newtons

MEDIUM/HIGH