

PROTECTIVE HEADWEAR



EVOGuard®C4-MAX Industrial Visor

ADA270-070-000 / ADA270-070-00C



ADA270-070-000



ADA270-070-00C
EVO VISTA Compatible



DESCRIPTION

EVOGuard®C high performance industrial visors provide comprehensive facial coverage without limiting movement. The optical class 1 visor range offers UV protection and a panoramic view with minimal distortion.

Fully compatible with EVOGuard® browguard systems and *EVO® helmet models, the C4-MAX visor offers up to AT rated impact protection and features an integral chinguard for added coverage.

*Excluding EVO®6100 range.

SAFETY STANDARDS

AS/NZS 1337

FEATURES

- EVOGuard® visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.
- High performance visors offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browguard.
- Visor filters harmful UV radiation to protect the eyes whilst also offering high light transmission and enhanced colour recognition.
- The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.
- EVOGuard® visors provide comprehensive facial coverage without limiting movement. EVOGuard® MAX visors offer enhanced coverage with an integral chinguard.
- Compatible with EVO® helmet models and EVOGuard® browguard systems. Visor supplied with dual system clips for mounting to a helmet or browguard.

SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN
filtering effect Scale Number
2C



Manufacturer's Trademark
JSP Dagger



High Energy Impact resists a 6 mm, 0.86g ball
@ 190 m/s Maximum protection for face shields
A - When Fitted to EVO® Helmet



The letter T, immediately after the mechanical
strength symbol, authorises use for high speed
particles at extreme temperatures. (-5°C and
+55°C) Optional
T



Resistance to Molten Metals and Hot Solids
Helmets (optional)
9



Resistance to fogging (optional)
N



BSI Kitemark
Yes



Product Weight
220g



Kit
Supplied With: EVO® 2,3,5,DS, Lite, Skyworker™
Arms. EVO8/EVOLite Badgeholder Arms.
EVOGuard® Browguard Mounting System.



LIGHT TRANSMISSION BREAKDOWN Lens
Shade number
1.2



Optical Class (1 – Class 1 – High quality for
regular use. 2 – Class 2 – Medium quality for
occasional use. 3 – Class 3 – Low quality for
exceptional use)
1



Medium Energy Impact resists a 6 mm, 0.86g
ball @ 120 m/s Maximum protection for goggles.
B - When Fitted To EVOGuard® Browguard



Protection from Liquid Splash
3



Resistance to Surface Damage by Fine Particles
(optional)
K



Visor Length
21.5cm

Material
Polycarbonate Shield



Recyclable
Yes

APPLICATIONS

Aerospace

Agricultural

Airports

Construction and Infrastructure

Facilities Management

Food and Drink Manufacturing

Manufacturing

Maritime

Mining, Aggregates and Quarrying

Rail and Tunnelling

Scaffolding and Roofing

Sole Trader

Utilities Contractors